

Acrylic Gap Filler



FILL & PAINT GAP FILLER

DESCRIPTION

A professional quality, paintable, acrylic gap filler that cures to form a durable, flexible seal for general purpose interior / exterior gap filling application. Fill & Paint has a smooth finish with low shrinkage and has good adhesion to most common building materials including wood, MDF, particle board, plywood, fibre cement sheet, plasterboard, concrete, masonry including brick and block work, cement render, polystyrene foam, tiles, ceramics, aluminum.

FEATURES & BENEFITS

- Paintable in 20 mins
- 10% Flexibility
- Non slump
- Water clean up
- External and internal

APPLICATIONS

Fill & Paint has many uses including: sealing around skirting boards, cornices, tiles (except showers), window frames, staircases, architraves, trims, wall & floorboards and coving. Sealing gaps and cracks in plastered wall and ceilings.

Technical Data	
Basis	Acrylic dispersion
Consistency	Paste
Curing system	Physical drying
Skin formation	20 min
Density	1.67 g/mL
Temperature resistance	-20 °C to 80 °C
Application temperature	5 °C to 30 °C
Maximum allowed distortion	10 %
Shrinkage	15%



Colour	Size
White	<input type="checkbox"/> 300 mL

Similar products in the industry

